

RP-120



MINIMUM / RECOMMENDED POWER:	25/35 HP	
MAX DIAMETER OF CUTTING	fresh soft wood:	120 mm 4.7 inch
	fresh hard wood:	110 mm 4.3 inch
	dry hard wood:	100 mm 3.9 inch
LENGTH OF CUTTING	6-blade mechanism:	8-15 cm 3.1-5.9 inch
	8-blade mechanism:	5-10 cm 2.0-3.9 inch
WEIGHT:	230 kg 507 Lbs.	



RP-150



MINIMUM / RECOMMENDED POWER:	45/80 HP	
MAX DIAMETER OF CUTTING	fresh soft wood:	140 mm 5.5 inch
	fresh hard wood:	130 mm 5.1 inch
	dry hard wood:	120 mm 4.7 inch
LENGTH OF CUTTING	6-blade mechanism:	12-18 cm 4.7-7.1 inch
	8-blade mechanism:	10-15 cm 3.9-5.9 inch
WEIGHT:	320 kg 705 Lbs.	



RP-200



MINIMUM / RECOMMENDED POWER:	90/150 HP	
MAX DIAMETER OF CUTTING	fresh soft wood:	160 mm 6.3 inch
	fresh hard wood:	150 mm 5.9 inch
	dry hard wood:	140 mm 5.5 inch
LENGTH OF CUTTING	6-blade mechanism:	18-30 cm 7.1-11.8 inch
	8-blade mechanism:	15-25 cm 5.9-9.8 inch
WEIGHT:	470 kg 1036 Lbs.	



ADDITIONAL ACCESSORIES

DOUBLE BAG HOLDER
for chippers without a conveyor belt



DOUBLE BAG HOLDER
for chippers with conveyor belt



ADJUSTABLE STAND FOR BIG BAG



RASCHEL BAGS



SPARE KNIVES/BLADES



FLYWHEEL-PULLEY SET WITH COVER
RP-120: ø360 mm, 3x17 mm, **40 kg**
RP-150: ø420 mm, 3x17 mm, **55 kg**
RP-200: ø500 mm, 4x17 mm, **80 kg**



ADAPTER WITH FRICTION CLUTCH
ADAPTER 4C - RP-120
ADAPTER 6C - RP-150
ADAPTER 8C - RP-200



PTO SHAFT WITH FRICTION CLUTCH
LINE 5C - RP-120
LINE 6C - RP-150
LINE 8C - RP-200



CONVEYOR 2.3m

RP-120



MINIMUM / RECOMMENDED POWER:	25/35 HP
MAX DIAMETER OF CUTTING	fresh soft wood: 120 mm 4.7 inch
	fresh hard wood: 110 mm 4.3 inch
	dry hard wood: 100 mm 3.9 inch
LENGTH OF CUTTING	6-blade mechanism: 8-15 cm 3.1-5.9 inch
	8-blade mechanism: 5-10 cm 2.0-3.9 inch
LENGTH / WIDTH CONVEYOR BELT:	230/25 cm 90.5/9.8 inch
WEIGHT:	310 kg 683 Lbs.



CONVEYOR 3m

RP-150



MINIMUM / RECOMMENDED POWER:	45/80 HP
MAX DIAMETER OF CUTTING	fresh soft wood: 140 mm 5.5 inch
	fresh hard wood: 130 mm 5.1 inch
	dry hard wood: 120 mm 4.7 inch
LENGTH OF CUTTING	6-blade mechanism: 12-18 cm 4.7-7.1 inch
	8-blade mechanism: 10-15 cm 3.9-5.9 inch
LENGTH / WIDTH CONVEYOR BELT:	300/30 cm 118.1/12.8 inch
WEIGHT:	440 kg 970 Lbs.



CONVEYOR 3m

RP-200



MINIMUM / RECOMMENDED POWER:	90/150 HP
MAX DIAMETER OF CUTTING	fresh soft wood: 160 mm 6.3 inch
	fresh hard wood: 150 mm 5.9 inch
	dry hard wood: 140 mm 5.5 inch
LENGTH OF CUTTING	6-blade mechanism: 18-30 cm 7.1-11.8 inch
	8-blade mechanism: 15-25 cm 5.9-9.8 inch
LENGTH / WIDTH CONVEYOR BELT:	300/30 cm 118.1/12.8 inch
WEIGHT:	600 kg 1323 Lbs.



SUPER

RP-200



MINIMUM / RECOMMENDED POWER:	70/100 HP
MAX DIAMETER OF CUTTING	fresh soft wood: 170 mm 6.7 inch
	fresh hard wood: 160 mm 6.3 inch
	dry hard wood: 150 mm 5.9 inch
LENGTH OF CUTTING	6-blade mechanism: 18-30 cm 7.1-11.8 inch
	8-blade mechanism: 15-25 cm 5.9-9.8 inch
FLYWHEEL WEIGHT:	80 kg 154 Lbs.
LENGTH / WIDTH CONVEYOR BELT:	400/40 cm 157.4/15.7 inch
WEIGHT:	800 kg 1764 Lbs.



RPS-120



ENGINE POWER: **27 HP**

MAX DIAMETER OF CUTTING
 fresh soft wood: **110 mm 4.3 inch**
 fresh hard wood: **100 mm 3.9 inch**
 dry hard wood: **90 mm 3.5 inch**

LENGTH OF CUTTING
 6-blade mechanism: **8-15 cm 3.1-5.9 inch**
 8-blade mechanism: **5-10 cm 2.0-3.9 inch**

WEIGHT: **290 kg 640 Lbs.**



CONVEYOR 3m



ENGINE POWER: **27 HP**

MAX DIAMETER OF CUTTING
 fresh soft wood: **110 mm 4.3 inch**
 fresh hard wood: **100 mm 3.9 inch**
 dry hard wood: **90 mm 3.5 inch**

LENGTH OF CUTTING
 6-blade mechanism: **8-15 cm 3.1-5.9 inch**
 8-blade mechanism: **5-10 cm 2.0-3.9 inch**

LENGTH / WIDTH CONVEYOR BELT: **230/25 cm 90.5/9.8 inch**

WEIGHT: **340 kg 750 Lbs.**



RPS-120



ENGINE POWER: **27 HP**

MAX DIAMETER OF CUTTING
 fresh soft wood: **110 mm 4.3 inch**
 fresh hard wood: **100 mm 3.9 inch**
 dry hard wood: **90 mm 3.5 inch**

LENGTH OF CUTTING
 6-blade mechanism: **8-15 cm 3.1-5.9 inch**
 8-blade mechanism: **5-10 cm 2.0-3.9 inch**

ROTATION OF WOODCHIPPERS: **360°**

LENGTH / WIDTH CONVEYOR BELT: **300/25 cm 118.1/9.8 inch**

WEIGHT: **460 kg 1014 Lbs.**



TURNTABLE

RPS-120



ENGINE POWER: **27 HP**

MAX DIAMETER OF CUTTING
 fresh soft wood: **110 mm 4.3 inch**
 fresh hard wood: **100 mm 3.9 inch**
 dry hard wood: **90 mm 3.5 inch**

LENGTH OF CUTTING
 6-blade mechanism: **8-15 cm 3.1-5.9 inch**
 8-blade mechanism: **5-10 cm 2.0-3.9 inch**

ROTATION OF WOODCHIPPERS: **360°**

LENGTH / WIDTH CONVEYOR BELT: **300/25 cm 118.1/9.8 inch**

WEIGHT: **640 kg 1411 Lbs.**



TRAILER

RPS-120



ELECTRIC MOTOR POWER:	11 kW
MAX DIAMETER OF CUTTING	fresh soft wood: 110 mm 4.3 inch
	fresh hard wood: 100 mm 3.9 inch
	dry hard wood: 90 mm 3.5 inch
LENGTH OF CUTTING	6-blade mechanism: 8-15 cm 3.1-5.9 inch
	8-blade mechanism: 5-10 cm 2.0-3.9 inch
WEIGHT:	250 kg 551 Lbs.

RPE-120



ELECTRIC MOTOR POWER:	11 kW
MAX DIAMETER OF CUTTING	fresh soft wood: 110 mm 4.3 inch
	fresh hard wood: 100 mm 3.9 inch
	dry hard wood: 90 mm 3.5 inch
LENGTH OF CUTTING	6-blade mechanism: 8-15 cm 3.1-5.9 inch
	8-blade mechanism: 5-10 cm 2.0-3.9 inch
LENGTH / WIDTH CONVEYOR BELT:	300/25 cm 118.1/9.8 inch
WEIGHT:	320 kg 1014 Lbs.

RPE-120 CONVEYOR 3m



ELECTRIC MOTOR POWER:	22 kW
MAX DIAMETER OF CUTTING	fresh soft wood: 160 mm 5.9 inch
	fresh hard wood: 150 mm 5.1 inch
	dry hard wood: 140 mm 4.3 inch
LENGTH OF CUTTING	6-blade mechanism: 18-30 cm 7.1-11.8 inch
	8-blade mechanism: 15-25 cm 5.9-9.8 inch
LENGTH / WIDTH CONVEYOR BELT:	300/30 cm 118.1/12.8 inch 400/40 cm 157.4/15.7 inch
WEIGHT:	950/1000 kg 2094/2205 Lbs.

RPE-200 CONVEYOR 4m

ADDITIONAL ACCESSORIES



DOUBLE BAG HOLDER
for chippers with conveyor belt

DOUBLE BAG HOLDER
for chippers without a conveyor belt



SPARE KNIVES/BLADES



FLYWHEEL-PULLEY SET WITH COVER
RPS-120, RPE-120
ø360 mm, 3x17 mm, 40 kg



ADJUSTABLE STAND FOR BIG BAG

RASCHEL BAGS

