

R-60



MINIMUM / RECOMMENDED POWER:		10/20 HP	
MAX DIAMETER OF CUTTING	fresh soft wood:	60 mm	2.4 inch
	fresh hard wood:	50 mm	2.0 inch
	dry hard wood:	40 mm	1.6 inch
LENGTH OF CUTTING	4-blade mechanism:	9-15 cm	3.5-5.9 inch
	6-blade mechanism:	5-10 cm	2.0-3.9 inch
WEIGHT:		120 kg	265 Lbs.



R-80



MINIMUM / RECOMMENDED POWER:		10/20 HP	
MAX DIAMETER OF CUTTING	fresh soft wood:	80 mm	3.1 inch
	fresh hard wood:	70 mm	2.6 inch
	dry hard wood:	60 mm	2.4 inch
LENGTH OF CUTTING	4-blade mechanism:	9-15 cm	3.5-5.9 inch
	6-blade mechanism:	5-12 cm	2.0-4.7 inch
WEIGHT:		130 kg	287 Lbs.



R-100



MINIMUM / RECOMMENDED POWER:		15/25 HP	
MAX DIAMETER OF CUTTING	fresh soft wood:	100 mm	3.9 inch
	fresh hard wood:	90 mm	3.5 inch
	dry hard wood:	80 mm	3.1 inch
LENGTH OF CUTTING	4-blade mechanism:	9-18 cm	3.5-7.1 inch
	6-blade mechanism:	7-14 cm	2.8-5.5 inch
WEIGHT:		145 kg	320 Lbs.



R-120



MINIMUM / RECOMMENDED POWER:		25/35 HP	
MAX DIAMETER OF CUTTING	fresh soft wood:	120 mm	4.7 inch
	fresh hard wood:	110 mm	4.3 inch
	dry hard wood:	100 mm	3.9 inch
LENGTH OF CUTTING	6-blade mechanism:	8-15 cm	3.1-5.9 inch
	8-blade mechanism:	5-10 cm	2.0-3.9 inch
WEIGHT:		170 kg	375 Lbs.



R-150



MINIMUM / RECOMMENDED POWER:		45/80 HP	
MAX DIAMETER OF CUTTING	fresh soft wood:	140 mm	5.5 inch
	fresh hard wood:	130 mm	5.1 inch
	dry hard wood:	120 mm	4.7 inch
LENGTH OF CUTTING	6-blade mechanism:	12-18 cm	4.7-7.1 inch
	8-blade mechanism:	10-15 cm	3.9-5.9 inch
WEIGHT:		290 kg	639 Lbs.





MINIMUM / RECOMMENDED POWER:	25/35 HP	
MAX DIAMETER OF CUTTING	fresh soft wood:	120 mm 4.7 inch
	fresh hard wood:	110 mm 4.3 inch
	dry hard wood:	100 mm 3.9 inch
LENGTH OF CUTTING	6-blade mechanism:	8-15 cm 3.1-5.9 inch
	8-blade mechanism:	5-10 cm 2.0-4.7 inch
LENGTH / WIDTH CONVEYOR BELT:	230/25 cm	90.5/9.8 inch
WEIGHT:	290 kg	639 Lbs.

R-120 CONVEYOR 2.3m



MINIMUM / RECOMMENDED POWER:	25/35 HP	
MAX DIAMETER OF CUTTING	fresh soft wood:	120 mm 4.7 inch
	fresh hard wood:	110 mm 4.3 inch
	dry hard wood:	100 mm 3.9 inch
LENGTH OF CUTTING	6-blade mechanism:	8-15 cm 3.1-5.9 inch
	8-blade mechanism:	5-10 cm 2.0-4.7 inch
LENGTH / WIDTH CONVEYOR BELT:	300/30 cm	118.1/12.8 inch
WEIGHT:	290 kg	639 Lbs.

R-120 CONVEYOR 3m



MINIMUM / RECOMMENDED POWER:	45/80 HP	
MAX DIAMETER OF CUTTING	fresh soft wood:	140 mm 5.5 inch
	fresh hard wood:	130 mm 5.1 inch
	dry hard wood:	120 mm 4.7 inch
LENGTH OF CUTTING	6-blade mechanism:	12-18 cm 4.7-7.1 inch
	8-blade mechanism:	10-15 cm 3.9-5.9 inch
LENGTH / WIDTH CONVEYOR BELT:	300/30 cm	118.1/12.8 inch
WEIGHT:	415 kg	915 Lbs.

R-150 CONVEYOR 3m

ADDITIONAL ACCESSORIES

DOUBLE BAG HOLDER
for chippers without a conveyor belt



FLYWHEEL-PULLEY SET WITH COVER
R-60, R-80: ø300 mm, 3x17 mm, 24 kg
R-100, R-120: ø360 mm, 3x17 mm, 40 kg
R-150: ø420 mm, 3x17 mm, 55 kg

PTO ADAPTER WITH FRICTION CLUTCH
ADAPTER 4C - R-60, R-80, R-100, R-120
ADAPTER 6C - R-150



DOUBLE BAG HOLDER
for chippers with conveyor belt



ADJUSTABLE STAND FOR BIG BAG



RASCHEL BAGS



SPARE KNIVES/BLADES



PTO SHAFT WITH CLUTCH (SHEAR BOLT)
LINE 4 - R-60, R-80



PTO SHAFT WITH FRICTION CLUTCH
LINE 4C - R-60, R-80
LINE 5C - R-100, R-120
LINE 6C - R-150



GASOLINE WOOD CHIPPERS

STANDARD



RS-80



ENGINE POWER:		7 HP	
MAX DIAMETER OF CUTTING	fresh soft wood:	75 mm	3.0 inch
	fresh hard wood:	65 mm	2.6 inch
	dry hard wood:	55 mm	2.2 inch
LENGTH OF CUTTING	4-blade mechanism:	9-15 cm	3.5-5.9 inch
	6-blade mechanism:	5-12 cm	2.0-4.7 inch
WEIGHT:		170 kg	375 Lbs.



RS-100



ENGINE POWER:		15 HP	
MAX DIAMETER OF CUTTING	fresh soft wood:	90 mm	3.5 inch
	fresh hard wood:	80 mm	3.1 inch
	dry hard wood:	70 mm	2.6 inch
LENGTH OF CUTTING	4-blade mechanism:	9-18 cm	3.5-7.1 inch
	6-blade mechanism:	7-14 cm	2.8-5.5 inch
WEIGHT:		225 kg	496 Lbs.



HYBRID



ENGINE POWER:		15 HP	
MINIMUM / RECOMMENDED POWER:		25/35 HP	
MAX DIAMETER OF CUTTING	fresh soft wood:	100/120 mm	3.9/4.7 inch
	fresh hard wood:	90/110 mm	3.5/4.3 inch
	dry hard wood:	80/100 mm	3.1/3.9 inch
LENGTH OF CUTTING	6-blade mechanism:	8-15 cm	3.1-5.9 inch
	8-blade mechanism:	5-10 cm	2.0-3.9 inch
WEIGHT:		270 kg	595 Lbs.



RS-120



ENGINE POWER:		15 HP	
MAX DIAMETER OF CUTTING	fresh soft wood:	100 mm	3.9 inch
	fresh hard wood:	90 mm	3.5 inch
	dry hard wood:	80 mm	3.1 inch
LENGTH OF CUTTING	6-blade mechanism:	8-15 cm	3.1-5.9 inch
	8-blade mechanism:	5-10 cm	2.0-3.9 inch
FLYWHEEL WEIGHT:		30 kg	66 Lbs.
WEIGHT:		360 kg	794 Lbs.



TRAILER



ENGINE POWER:		15 HP	
MAX DIAMETER OF CUTTING	fresh soft wood:	100 mm	3.9 inch
	fresh hard wood:	90 mm	3.5 inch
	dry hard wood:	80 mm	3.1 inch
LENGTH OF CUTTING	6-blade mechanism:	8-15 cm	3.1-5.9 inch
	8-blade mechanism:	5-10 cm	2.0-3.9 inch
FLYWHEEL WEIGHT:		30 kg	66 Lbs.
PLATFORM TRAILER:		for registration	





ELECTRIC MOTOR POWER:	5.5 kW	
MAX DIAMETER OF CUTTING	fresh soft wood:	75 mm 3.0 inch
	fresh hard wood:	65 mm 2.6 inch
	dry hard wood:	55 mm 2.2 inch
LENGTH OF CUTTING	4-blade mechanism:	9-15 cm 3.5-5.9 inch
	6-blade mechanism:	5-12 cm 2.0-4.7 inch
WEIGHT:	180 kg	397 Lbs.

RE-80



ELECTRIC MOTOR POWER:	7,5 kW	
MAX DIAMETER OF CUTTING	fresh soft wood:	90 mm 3.5 inch
	fresh hard wood:	80 mm 3.1 inch
	dry hard wood:	70 mm 2.6 inch
LENGTH OF CUTTING	4-blade mechanism:	9-18 cm 3.5-7.1 inch
	6-blade mechanism:	7-14 cm 2.8-5.5 inch
WEIGHT:	240 kg	529 Lbs.

RE-100



ELECTRIC MOTOR POWER:	7,5 kW	
MINIMUM / RECOMMENDED POWER:	25/35 HP	
MAX DIAMETER OF CUTTING	fresh soft wood:	100/120 mm 3.9/4.7 inch
	fresh hard wood:	90/110 mm 3.5/4.3 inch
	dry hard wood:	80/100 mm 3.1/3.9 inch
LENGTH OF CUTTING	6-blade mechanism:	8-15 cm 3.1-5.9 inch
	8-blade mechanism:	5-10 cm 2.0-3.9 inch
WEIGHT:	290 kg	639 Lbs.

HYBRID

RE-120

ADDITIONAL ACCESSORIES

DOUBLE BAG HOLDER



FLYWHEEL-PULLEY SET WITH COVER
RS-80, RS-100, RE-80, RE-100
ø300 mm, 3x17 mm, 24 kg



PTO ADAPTER WITH FRICTION CLUTCH ADAPTER 4C
RS-120 HYBRID, RE-120 HYBRID



SPARE KNIVES/BLADES



PTO SHAFT WITH FRICTION CLUTCH LINE 5C
RS-120 HYBRID, RE-120 HYBRID

